

saxun
by Giménez Ganga

Bioclimatic
Pergolas

P-190

P-150



saxun[°]
Your world, our universe.

Saxun contributes to the well-being and happiness of people through solutions that improve the spaces in your life. We are in love with spaces and the possibilities they offer us to help us feel good. That's why we develop products that are functional, versatile and comfortable, so that you can make the most of your space in a variety of ways.






Sharing unique moments

Creating - or making the most of - new spaces to enjoy with the family, or expanding the possibilities of your restaurant throughout the year, regardless of the heat or cold, rain or snow, are some of the privileges that we're not going to give up nowadays.

Saxun offers you the most successful solution, with the best market potential when it comes to enjoying your terrace or garden as though it were another living room in your home.

Our P-190 and P-150 bioclimatic pergolas allow you to enjoy outdoor living all year round, regulating the temperature of the room in a natural way, while protecting it from changes in the weather.

Robust sun protection and enclosure systems that are easy to install, require a minimum amount of maintenance and have a long service life.



High performance protection

The P-190 and P-150 bioclimatic pergolas are robust sun protection systems that protect from the rain and provide pleasant ventilation to the space created.

Structures that are easy to install and require virtually no maintenance.



Total protection against solar radiation and rain.



Moveable slats from 0 to 135°.



The movement of the slats is motorised.



Simple and convenient operation by means of the latest generation of transmitters and automated systems.



Patented perimeter sealing system for rain and light.



Modular system with great customisation possibilities.



LED lighting in the perimeter area and/or in slats.



Bluetooth sound system Speakers built into the structure.



Infrared heater for the coldest days.



It allows the addition of other Saxun systems, such as awnings, glass sliding windows, drop awnings, window and door shutters...



Top quality aluminium and stainless steel components.






Bioclimatic effect


The slats of our bioclimatic pergolas rotate from a closed position to an open position, up to 135°.

The system generates pleasant natural ventilation by heating the louvres when they are exposed to solar radiation. This produces a natural convection movement of air from the bottom up, through the slats.


An adjustable effect by turning the slats, with which we also control the entry of the desired sunlight into the space created by the pergola itself.



0° The roof is sealed and provides total protection against the most harmful solar radiation, as well as the most extreme weather conditions.



5° It permits excellent room ventilation, maintaining shade when it is sunny, or protecting against water when it rains.



45° Enjoy natural ventilation, controlling the direction of the sun's rays and their intensity.

90° Opening the slats allows full use of the light, even when it is scarce.

135° Maximum inclination that lets sunlight come through even when it starts getting dark.

Bioclimatic Pergola

P-190 and P-150



The bioclimatic pergola is a sun protection system with a clean-lined design that can be adapted to all architectural styles.

The system is based on a ceiling of adjustable slats made of extruded aluminium. The slats rotate from 0° to 135° thanks to the pivoting shafts inserted in the ends of the slats, which are driven by a 24 VDC mechanical motor. They are operated by means of an extruded aluminium plate.

This mobile roof is mounted on an extruded aluminium structure that allows endless possibilities of modulation, offering optimum resistance to rain and snow loads.


Collecting rainwater

The design of our pergolas' slats allows rainwater to be collected in order to reuse it. Water is channelled towards the lateral frames, without needing a slope to drain.




Waterproof system

The slats contain a rubber seal that ensures the waterproofing of the pergola, as the seal does not allow water into the joints between the slats. At the same time, it cancels the noise created between the slats due to vibration caused by wind.




Registered perimeter seal

A registered system that acts against sideways rain and that also does not allow direct light and/or reflected light to pass through the joints between the slats, or between the slats and the frame.




Motorised operation

The pergola can be operated only by motorisation, using a 24 VDC motor with IP 67 protection. This will also ensure your safety against electric shock, with the additional safety of earthing protection.





Collecting rainwater




The design of the P-190 and P-150 slats allows rainwater to be collected in order to reuse it.

Water is channelled towards the frames, without needing a slope to drain.

The profiles form a channel that guides the water through them.


Free-flow drainage

In the case of free-flow drainage, water is expelled freely by means of two columns towards the surface where the pergola is mounted, through the holes for this purpose.



Slab channel drainage

The built-in channelling inside allows rainwater to be evacuated and then recovered later. The pre-installed draining pipes must be taken into account during the construction of the slab, prior to mounting the pergola.





P-190

Bioclimatic Pergola

It has endless modulation possibilities, which added to the quality of its materials makes it the perfect solution for solar protection, ideal for adapting and enhancing every architectural style where it is installed.

Maximum dimensions

- A** Maximum tested width
- B** Maximum tested length
- C** Maximum height
- D** Beam dimensions
- E** Beam dimensions
- F** Column dimensions
- G** Minimum inclination
- H** Type of drainage




Table of maximum dimensions according to type of Bioclimatic Pergola

	4 Columns	3 Columns	2 Columns		DUPLEX		No Columns
			Parallel to wall	Perpendicular to wall	2 columns	4 columns	
A	4,200 mm	4,200 mm	4,200 mm	4,200 mm	7,000 mm	7,000 mm	4,200 mm
B	6,200 mm	6,200 mm	6,200 mm	6,200 mm	6,000 mm	6,000 mm	6,200 mm
C	3,000 mm	3,000 mm	3,000 mm	3,000 mm	3,000 mm	3,000 mm	-
D	220 mm	220 mm	220 mm	220 mm	282.5 mm	282.5 mm	220 mm
E	220 mm	220 mm	220 mm	220 mm	220 mm	220 mm	220 mm
F	150x150 mm	150x150 mm	150x150 mm	150x150 mm	150x150 mm	150x150 mm	-
G	0%	0%	0%	0%	0%	0%	0%
H	Free-flow or slab channelling.						To be done by client


Tests

Our pergolas, just like the rest of our products, are subjected to a variety of tests in our labs in order to check their resistance and behaviour under every type of circumstance.

Test results

☁️ Wind load EN 13659	Class 6
☔ Rain load EN 12056-3	108 l · m²/h (structure and slats)
❄️ Snow load EN 1999 Eurocode 9	100 kg/m²

Features




Motor

The motorised element is discretely hidden between the slats and the frame, enhancing the beauty of the pergola.




Profiles

Slats




P-190 LED slat
050189




P-190 slat
050188

Beams




Beam
P-282,50x100
Front duplex pergola
050496




Beam P-220x100
Pergola simplex and
duplex lateral
023103

Columns




Column
P-150x150x2.5
023101

Adapters




Clip-on adapter
40x75
050327



Clip-on adapter 40x50
SOFT
050218


Profiles




Profile "U"
62x65x2.5
050155



Transmission plate
30x4
507162



Perimeter
LED profile
050491



Clipping
collector
050208

* Measurements in mm.



P-150

Bioclimatic Pergola

Very advantageous when it comes to installation. Installation time is minimised, making it a quick and easy task, since some profiles simply clip into place and do not need screws.

The mounting of the slats is also smoother, thanks to the retracting spring-loaded shaft.

Maximum dimensions

- A Maximum tested width
- B Maximum tested length
- C Maximum height
- D Beam dimensions
- E Beam dimensions
- F Column dimensions
- G Minimum inclination
- H Type of drainage




Table of maximum dimensions according to type of Bioclimatic Pergola

	4 Columns	3 Columns	2 Columns		DUPLEX		No Columns
			Parallel to wall	Perpendicular to wall	2 columns	4 columns	
A	3,600 mm	3,600 mm	3,600 mm	3,600 mm	6,000 mm	6,000 mm	3,600 mm
B	5,000 mm	5,000 mm	5,000 mm	5,000 mm	5,000 mm	5,000 mm	5,000 mm
C	3,000 mm	3,000 mm	3,000 mm	3,000 mm	3,000 mm	3,000 mm	-
D	180 mm	180 mm	180 mm	180 mm	242.50 mm	242.50 mm	180 mm
E	180 mm	180 mm	180 mm	180 mm	180 mm	180 mm	180 mm
F	150x150 mm	150x150 mm	150x150 mm	150x150 mm	150x150 mm	150x150 mm	-
G	0%	0%	0%	0%	0%	0%	0%
H	Free-flow or slab channelling.						To be done by client


Tests

Our pergolas, just like the rest of our products, are subjected to a variety of tests in our labs in order to check their resistance and behaviour under every type of circumstance.

Test results

☁️ Wind load EN 13659	Class 6
☔ Rain load EN 12056-3	108 l · m²/h (structure and slats)
❄️ Snow load EN 1999 Eurocode 9	65 kg/m²


Features



Motor


In this model, the motor is located in the upper part of the pergola, on the outside, so it is not visible from inside.

This arrangement makes it possible to share a motor when there are groups of pergolas, or in duplex pergolas.




Profiles

Slats




P-150 LED slat
050210




P-150 slat
050209


Beams



Beam
P-242,50x100
Front duplex pergola
050249




Beam P-180x85
Pergola simplex and
duplex lateral
050206




Double beam
P-180x150
Duplex central pergola
050485

Columns




Column
P-150x150x2.5
023101

Adapters




Clip-on adapter
40x75
050327



Clip-on adapter 40x50
SOFT
050218


Profiles




Profile "U"
62x65x2.5
050155



Transmission plate
profile
30x4
507162




Perimeter
LED profile
050491




Clipping
collector
050208

* Measurements in mm.


Types of assembly




● Bioclimatic pergola
no columns




● Bioclimatic Pergola
2 duplex columns




● Bioclimatic pergola
4 columns




● Bioclimatic pergola
3 columns



● Bioclimatic Pergola
2 columns with parallel slats



● Bioclimatic Pergola
2 columns with perpendicular slats



● Bioclimatic Pergola
4 duplex columns

Customised configuration


Terraces, patios and gardens of all types of homes, restaurants and hotels enjoy outdoor spaces protected with Saxun, thanks to the endless possibilities offered by P-190 and P-150.

The proven experience of our Technical Office provides you with the advice you need to find the right solution for each space.



Examples of custom installations


Duplex pergolas sharing columns




Pergolas combining movable and fixed slats



Pergolas without sharing columns




Pergola sharing columns with central steel structure



Pergolas with offset columns



Pergolas with offset beams



Great allies of hoteliers

Our bioclimatic pergolas are a safe bet for all types of projects in the HORECA sector, whether in hotels, restaurants or cafeterias.

Without requiring any brickwork, and the fact they are considered collapsible structures allows for quick and easy installation.

A wide range of colours and finishes, as well as accessories and complementary items, enable the creation of new and attractive spaces for your clients to enjoy being outdoors in any season of the year, at any time of day.





Prescription and projects


A must in the new architecture

The installation of this product is quick and practically non-invasive, with no need for masonry work. This makes our bioclimatic pergolas the star solution in terms of sun protection and enclosure systems.

Architects and designers all over the world are including Saxun pergolas in all types of architectural projects, both new and refurbished, whether on penthouse terraces or in the gardens of single-family homes.

P-190 and P-150 are indispensable systems for projects of all sizes in the hotel and catering industry.


To this end, we provide all the necessary resources so that designers can include these products in the initial phase of the project; BIM files, dwg and prescription sheets to conceptualise new spaces from the very beginning.



Data sheet.

A universe full of possibilities

The stability and robustness of this extruded aluminium structure allows the installation of other Saxun solutions to increase the possibilities of your space.



Awning

The installation of cassette awnings, such as Kiara, will extend your sun protection and at the same time your pergola will gain greater aesthetic value.

Wind Screen

With the Wind Screen installed along the perimeter, a barrier against the most horizontal solar incidence is ensured. By adding this Saxun product you will get a more sheltered and intimate space.

Window and Door Shutters

Folding window and door shutters, such as Éforus, form an enclosure that can be opened both by folding down the leaves and by opening the slats.



Glass sliding window

For all those sheltered spaces where we don't want to lose one iota of visibility to the outside, the Astron glass sliding window is the solution of choice.



LED lighting

new

Choose between RGB lights or warm light with our new LED strips.

Give an elegant touch to the Pergola with the new spotlights and light fixtures.

The new lighting options help create spaces with greater ambience possibilities; more welcoming, and ideal for residential use as well as for restaurants and hotels.

New LED strips (both for slats and the structure's perimeter), portholes and fittings for columns, which increase the value of your Pergola. Installation of these new accessories is also much more convenient and quicker for professionals.




Quick assembly




Easy installation




Enhanced aesthetic




Perimeter LED



LED strip on slats



Portholes





Fittings

Colours and finishes

Your pergola, the way you imagine it

To adapt to all aesthetic requirements or to create totally disruptive spaces, the choice of colour is fundamental. This is why your Saxun pergola has no limits; you can choose any colour from the RAL chart, anodised colours and woods, in glossy, matt and textured finishes (for even greater weather resistance).

A customised finish that guarantees excellent performance against solar radiation, rain or snow, thanks to the quality of the aluminium, the paint used, and the lacquering process itself.



Our state-of-the-art lacquering process is based on Qualicoat prescriptions (international quality seal for lacquered aluminium that guarantees its quality for use in architecture) and allows a wide variety of processes and high-performance finishes that adapt to every requirement:

- General multi-metal process (not Qualicoat).
- Equivalent to standard Qualicoat.
- For installations exposed to the sea, we can offer a superior quality of Qualicoat, which is the Seaside Class. Within this classification, the AA1 fully coincides with the Qualimarine seal, awarded by the French Association (ADAL).






Saxun offers the widest range of enclosures, solar protection and decorative treatments on the market to improve the spaces in your life, accommodating your needs and style, so that you can feel secure and at ease.



saxun
by Giménez Ganga

Giménez Ganga, S.L.U.
Polígono Industrial El Castillo
C/ Roma, 4
03630 • Sax (Alicante) • Spain

saxun.com



Your world,
our universe.

